

Hyperview 1.67 Aspheric Progressive (regular corridor) Blank



Diameter (mm)	Nominal convex curve (D)	Power range (D)	Convex curve radius (mm)	Actual convex curve (N=1.53) (D)	Sagitta depth Gauge 50mm bell (mm)	Nominal concave curve (N=1.53) (D)	Center Thickness (mm)	Edge Thickness (mm)	Add Powers in 0.25 D steps (D)
70 / 75	1.50	-15.00 to -10.25	442,67	1,20	0,71	9,30	16,0	26,5	0.75 to 3.50
75 / 80	2.50	-10.00 to -6.25	265,60	2.00	1.18	9.30	9.0	20.3	0.75 to 3.50
75 / 80	3.80	-6.00 to -4.25	179,46	2.95	1.75	8.49	4.0	12.4	0.75 to 3.50
75 / 80	4.80	-4.00 to +2.00	132,80	3.99	2.37	7.98	5.7	11.7	0.75 to 3.50
75 / 80	6.40	+2.25 to +4.00	103,75	5.11	3.06	5.81	8.3	8.9	0.75 to 3.50
75 / 80	8.00	+4.25 to +6.00	81,98	6.46	3.91	5.81	10.7	8.9	0.75 to 3.50

Minimum fitting height: 22 mm
Length of transition corridor: 16 mm

