

Hyperview 1.67 Aspheric Progressive (short corridor) Blank



Diameter (mm)	Nominal convex curve (D)	Power range at main meridian (D)	Actual convex curve (N=1.53) (D)	Radius of curvature (mm)	Sagitta depth gauge 50mm bell (mm)	Nominal concave curve (N=1.53) (D)	Center thickness (mm)	Edge thickness (mm)	Add powers in 0,25 steps (D)
70 / 75	1.50	-15.00 to -10.25	1,20	442,67	0,71	9,30	9,7	20,3	0.75 to 3.50
75 / 80	2.50 N	-10.00 to -6.25	2,00	265,60	1,18	7,98	6,1	15,0	0.75 to 3.50
75 / 80	2.50	-10.00 to -6.25	2,00	265,60	1,18	9,30	9,0	20,3	0.75 to 3.50
75 / 80	3.80	-6.00 to -4.25	2,95	179,46	1,75	8,49	4,0	12,4	0.75 to 3.50
75 / 80	4.80	-4.00 to +2.00	3,99	132,80	2,37	7,98	5,7	11,7	0.75 to 3.50
75 / 80	6.40	+2.25 to +4.00	5,11	103,75	3,06	5,81	8,3	8,9	0.75 to 3.50
75 / 80	8.00	+4.25 to +6.00	6,46	81,98	3,91	5,81	10,7	8,9	0.75 to 3.50

Minimum fitting height: 17 mm
Length of transition corridor: 12 mm

