

# Hyperview 1.60/42 Aspheric Progressive (regular corridor) Blank



| Diameter<br>(mm) | Nominal<br>convex curve<br>(D) | Power range at<br>main meridian<br>(D) | Actual<br>convex curve<br>(N=1.53)<br>(D) | Radius of<br>curvature<br>R1<br>(mm) | Sagitta depth<br>gauge<br>50mm bell<br>(mm) | Nominal<br>concave curve<br>(N=1.53)<br>(D) | Center<br>thickness<br>(mm) | Edge<br>thickness<br>(mm) | Add.<br>powers<br>in<br>0.25 D steps |
|------------------|--------------------------------|--|---|--------------------------------------|---|---|-----------------------------|---------------------------|--------------------------------------|
| 70/75            | 2.2                            | -6.25 to -10.00                        | 1,94                                      | 272,73                               | 1,148                                       | 9,3   | 10,4                        | 20,0                      | 0.75 to 3.50                         |
| 75/80            | 3.5                            | -4.25 to -6.00                         | 3,09                                      | 171,43                               | 1,833                                       | 8,0   | 7,2                         | 14,5                      | 0.75 to 3.50                         |
| 75/80            | 4.7                            | +2.00 to -4.00                         | 4,15                                      | 127,66                               | 2,472                                       | 6,9   | 9,0                         | 13,0                      | 0.75 to 3.50                         |
| 75/80            | 6.2                            | +4.00 to +2.25                         | 5,48                                      | 96,77                                | 3,285                                       | 4,8   | 8,9                         | 8,0                       | 0.75 to 3.50                         |
| 75/80            | 8.2                            | +6.00 to +4.25                         | 7,24                                      | 73,17                                | 4,403                                       | 4,8   | 11,8                        | 8,0                       | 0.75 to 3.50                         |

Minimum fitting height: 22 mm  
Length of transition corridor: 16 mm

