

## 1.50 Spherical Bifocal Flat Top S28 Blank 65 / 70 mm

**ASAHI-LITE®**

Diameter (mm)	Nominal convex curve (D)	Power range at main meridian (D)	Actual convex curve (N=1.53) (D)	Radius of curvature R1 (mm)	Sagitta depth gauge 50mm bell (mm)	Actual concave curve (N=1.53) (D)	Center thickness (mm)	Edge thickness (mm)	Add. powers in 0.25 D steps
70	0.50	-5.25 to -10.00	0,54	981,48	0,318	5,70	10,0	16,0	0.50 to 4.00
70	0.50 SFX	-10.25 to -14.00	0,54	981,48	0,318	2,06	17,7	20,0	0.50 to 4.00
70	2.00	-2.00 to -5.00	2,02	262,38	1,194	5,70	11,6	16,0	0.50 to 4.00
70	4.00	-1.00 to -3.00	3,92	135,20	2,331	5,70	6,8	9,0	0.50 to 4.00
70	5.00	+1.00 to -2.00	5,06	104,74	3,027	5,70	8,4	9,0	0.75 to 4.00
70	6.00	+2.00 to -2.00	6,06	87,46	3,649	5,70	9,5	9,0	0.50 to 4.00
70	7.00	+0.00 to +4.00	7,07	74,96	4,292	5,70	10,5	9,0	0.50 to 4.00
70	8.00	+2.00 to +5.00	8,05	65,84	4,931	5,70	10,0	7,0	0.50 to 4.00
70	8.00 SFX	+2.00 to +5.00	8,05	65,84	4,931	5,70	11,0	8,0	0.50 to 4.00
70	10.00	+5.25 to +7.00	10,09	52,53	6,330	5,70	13,0	7,0	0.50 to 4.00
65	12.00	+7.25 to -+9.00	12,00	44,17	7,756	5,70	17,0	7,0	1.00 to 3.50
65	14.00	+9.25 to +12.00	14,00	37,86	9,428	5,70	23,0	7,0	1.00 to 3.50

