

1.50 Spherical Blended Bifocal Round Top Blank

ASAHI-LITE®

Diameter (mm)	Nominal convex curve (D)	Power range at main meridian (D)	Actual convex curve (N=1.53) (D)	Radius of curvature R1 (mm)	Sagitta depth gauge 50mm bell (mm)	Nominal concave curve (N=1.53) (D)	Center thickness (mm)	Edge thickness (mm)	Add. powers in 0.25 D steps
70 / 24mm	4.00	-1.00 to -3.00	3,90	135,90	2,319	5,70	6,5	8,5	1.00 to 3.50
70 / 24mm	6.00	+2.00 to -2.00	6,02	88,04	3,624	5,70	8,8	8,5	1.00 to 3.50
70 / 24mm	8.00	+2.00 to +5.00	8,03	66,00	4,918	5,70	10,0	7,0	1.00 to 3.50
70 / 26mm	4.00	-1.00 to -3.00	3,92	135,20	2,331	5,70	6,5	9,0	1.00 to 3.50
70 / 26mm	6.00	+2.00 to -2.00	6,02	88,04	3,624	5,70	9,0	8,5	1.00 to 3.50
70 / 26mm	8.00	+2.00 to +5.00	8,03	66,00	4,918	5,70	10,0	7,0	1.00 to 3.50
70 / 28mm	2.00	-2.00 to -5.00	2,02	262,38	1,194	5,70	6,0	11,0	1.00 to 3.50
70 / 28mm	4.00	-1.00 to -3.00	3,92	135,20	2,331	5,70	7,0	9,0	1.00 to 3.50
70 / 28mm	6.00	+2.00 to -2.00	6,03	87,89	3,630	5,70	9,5	9,0	1.00 to 3.50
70 / 28mm	8.00	+2.00 to +5.00	8,06	65,76	4,938	5,70	10,0	7,0	1.00 to 3.50

