

1.50 Spherical Single Vision Blank 65 mm

ASAHI-LITE®

Diameter (mm)	Nominal convex curve (D)	Power range at main meridian (D)	Actual convex curve (N=1.530) (D)	Radius of curvature R1 (mm)	Sagitta depth gauge 50 mm bell (mm)	Center thickness (mm)	Edge thickness (mm)
65	Plano	-8.00 to -12.00	0,00	26.500,00	0,01	10,3	16,0
65	0.50	-8.00 to -12.00	0,53	1.000,00	0,31	7,5	13,0
65	1.50	-6.00 to -10.00	1,51	350,99	0,89	11,8	16,0
65	2.00	-5.25 to -8.00	2,15	246,51	1,27	12,2	16,0
65	3.00	-4.25 to -6.00	2,98	177,85	1,77	9,5	13,0
65	4.00	-2.25 to -5.00	3,68	144,02	2,19	11,0	13,0
65	5.00	+1.00 to -3.00	4,79	110,65	2,86	12,0	13,0
65	6.00	+2.00 to -2.00	5,90	89,83	3,55	8,0	7,5
65	7.00	+2.00 to +4.00	6,87	77,15	4,16	9,0	7,5
65	8.00	+2.25 to +5.00	7,95	66,67	4,87	10,3	7,5
65	9.00	+5.00 to +8.00	8,94	59,28	5,53	11,6	7,5
65	10.00	+6.00 to +10.00	10,04	52,79	6,30	13,0	7,5
65	11.00	+6.00 to +11.00	11,20	47,32	7,14	15,0	7,5
65	12.00	+7.00 to +11.00	12,40	42,74	8,07	15,5	7,0
65	14.00	+8.00 to +13.00	14,22	37,27	9,63	18,5	7,0