

## 1.50 Spherical Single Vision Blank 70 mm

**ASAHI-LITE®**

Diameter (mm)	Nominal convex curve (D)	Power range at main meridian (D)	Actual convex curve (N=1.530) (D)	Radius of curvature R1 (mm)	Sagitta depth gauge 50 mm bell (mm)	Center thickness (mm)	Edge thickness (mm)
70	Plano	-8.00 to -12.00	0,03	26.500,00	0,01	9,3	16,0
70	0.50	-7.00 to -9.00	0,53	1.000,00	0,31	10,2	16,0
70	1.50	-6.00 to -10.00	1,56	339,74	0,92	11,0	16,0
70	2.00	-5.25 to -8.00	2,17	244,24	1,28	11,5	16,0
70	3.00	-4,25 to -6.00	2,99	177,26	1,77	9,3	12,5
70	4.00	-2.25 to -5.00	3,69	143,63	2,19	9,1	11,5
70	5.00	+1.00 to -3.00	4,81	110,19	2,87	11,8	13,0
70	6.00	+2.00 to -2.00	5,90	89,83	3,55	8,2	8,0
70	7.00	+2.00 to +4.00	6,90	76,81	4,18	9,0	7,5
70	8.00	+2.25 to +5.00	7,97	66,50	4,88	9,6	7,0
70	9.00	+5.00 to +8.00	8,95	59,22	5,54	11,2	7,5
70	10.00	+6.00 to +10.00	10,07	52,63	6,32	13,0	6,5