

## Hyper Index 1.74/33 Aspheric Single Vision Blank

**ASAHI-LITE®**

Diameter (mm)	Nominal convex curve (D)	Power range at main meridian (D)	Actual convex curve (N = 1.53) (D)	Radius of curvature R1 (mm)	Sagitta depth gauge 50mm bell (mm)	Nominal concave curve (N = 1.53) (D)	Center thickness (mm)	Edge thickness (mm)
65	0.50EX	-15.25 - -18.00	0,40	1.320,00	0,338	10,52	10,0	21,2
65	0.50S	-12.25 - -15.00	0,40	1.320,00	0,338	8,17	8,8	16,8
70	0.50	-8.25 - -12.00	0,38	1.390,57	0,300	7,78	5,2	14,2
75	1.50	-4.75 - -8.00	1,02	519,01	0,756	5,90	5,4	11,9
75	3.00	-0.00 - -4.50	2,15	246,49	1,331	5,20	4,4	8,5
75	4.00	+0.25 - +1.00	2,88	184,25	1,686	4,76	5,5	8,3
75	4.50	+1.25 - +2.00	3,24	163,78	1,844	4,76	5,5	8,0
70	5.00	+2.25 - +3.00	3,57	148,29	2,035	4,59	5,5	7,1
70	5.50	+3.25 - +4.00	3,90	135,98	2,185	4,59	5,5	6,8
70	5.90	+4.25 - +5.00	4,28	123,87	2,366	4,59	6,5	6,7
70	6.90	+5.25 - +6.00	4,96	106,81	2,762	4,59	7,3	6,8
65	7.80	+6.25 - +7.00	5,64	94,01	3,157	3,29	7,9	6,1
65	8.80	+7.25 - +8.00	6,31	83,94	3,530	3,29	8,5	6,1
65	9.70	+8.25 - +9.00	6,98	75,90	3,916	3,29	9,2	6,1
65	10.60	-9.25 - +10.00	7,61	69,66	4,290	3,29	9,8	6,1