SELECT Clear Vision 1.50 CR-39 SPH 65 mm

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Minus SPH

UV360 & UV400 available | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
0.00																	
-0.25																	
-0.50																	
-0.75																	
-1.00																	
-1.25																	
-1.50																	
-1.75																	
-2.00																	
-2.25																	
-2.50																	
-2.75																	
-3.00																	
-3.25																	
-3.50																	
-3.75																	
-4.00																	
-4.25																	
-4.50																	
-4.75																	
-5.00																	
-5.25																	
-5.50																	
-5.75																	
-6.00																	
-6.25																	
-6.50																	
-6.75																	
-7.00																	
-7.25																	
-7.50																	
-7.75																	
-8.00																	
-8.25																	
-8.50																	
-8.75																	
-9.00																	
-9.25																	
-9.50																	
-9.75																	
-10.00																	

Ø65 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

SELECT Clear Vision 1.50 CR-39 SPH 65 mm

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Plus SPH

UV360 & UV400 available | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
+0.25																	
+0.50																	
+0.75																	
+1.00																	
+1.25																	
+1.50																	
+1.75																	
+2.00																	
+2.25																	
+2.50																	
+2.75																	
+3.00																	
+3.25																	
+3.50																	
+3.75																	
+4.00																	
+4.25																	
+4.50																	
+4.75																	
+5.00																	
+5.25																	
+5.50																	
+5.75																	
+6.00																	
+6.25																	
+6.50																	
+6.75																	
+7.00																	
+7.25																	
+7.50																	
+7.75																	
+8.00																	
+8.25																	
+8.50																	
+8.75																	
+9.00																	
+9.25																	
+9.50																	
+9.75																	
+10.00																	

Ø65 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

SELECT Clear Vision 1.50 CR-39 SPH 65 mm

Finished | SPH

CR-39 | UV360 & UV400 available | Made in China

MINUS POWER (-,-)					SPH POWER	PLUS POWER (+,-)				
THICKNESS(mm)		BASE CURVE		DIA		DIA	BASE CURVE		THICKNESS(mm)	
CT	ET	FC	BC				FC	BC	C.T	E.T
2	2.0	500	500		0.00					
2	2.3	475	500	65mm	0.25	65mm	525	500	2.2	1.9
2	2.5	450	500		0.50		550	500	2.5	1.9
1.9	2.7	425	500		0.75		575	500	2.7	1.9
1.9	3.0	400	500		1.00		600	500	2.5	1.4
1.8	3.2	375	500		1.25		575	450	2.8	1.4
1.8	3.4	350	500		1.50		600	450	2.9	1.2
1.8	3.7	325	500		1.75		625	450	3.2	1.2
1.8	4.0	300	500		2.00		650	450	3.5	1.2
1.7	4.2	275	500		2.25		625	400	3.7	1.2
1.7	4.4	250	500		2.50		650	400	4	1.2
1.7	4.7	225	500		2.75		675	400	4.3	1.2
1.7	5.0	200	500		3.00		700	400	4.7	1.2
1.7	5.2	175	500		3.25		625	300	4.9	1.2
1.7	5.5	150	500		3.50		650	300	5.1	1.2
1.7	5.9	275	650		3.75		675	300	5.4	1.2
1.6	6.1	250	650		4.00		700	300	5.8	1.2
1.6	6.4	225	650		4.25		625	200	5.9	1.2
1.6	6.7	200	650		4.50		650	200	6.2	1.2
1.6	7.0	225	700		4.75		675	200	6.5	1.2
1.6	7.3	200	700		5.00		700	200	6.8	1.2
1.6	7.5	175	700		5.25		725	200	7.1	1.2
1.6	7.8	150	700		5.50		750	200	7.5	1.2
1.6	8.1	125	700		5.75		775	200	7.8	1.2
1.6	8.3	100	700		6.00		800	200	8.1	1.2
1.6	12.5	150	1000	65mm	8.50		1050	200	11.0	1.2
1.6	13.1	100	1000		9.00		1100	200	11.7	1.2
1.6	14.3	150	1100		9.50		1150	200	12.4	1.2
1.6	14.8	100	1100		10.00		1200	200	13.4	1.2