SELECT Clear Vision 1.56 Mid Index SPH

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Minus SPH

UV400 | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
0.00		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-0.25		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-0.50		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-0.75		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-1.00		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-1.25		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-1.50		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-1.75		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-2.00		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-2.25		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-2.50		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-2.75		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-3.00		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-3.25		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-3.50		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-3.75		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-4.00		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-4.25		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-4.50		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-4.75		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-5.00		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-5.25		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-5.50		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-5.75		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-6.00		D	D	D	D	D	D	D	D	C	C	C	C	C	C	C	C
-6.25		C	C	C	C	C	C	C	C								
-6.50		C	C	C	C	C	C	C	C								
-6.75		C	C	C	C	C	C	C	C								
-7.00		C	C	C	C	C	C	C	C								
-7.25		C	C	C	C	C	C	C	C								
-7.50		C	C	C	C	C	C	C	C								
-7.75		C	C	C	C	C	C	C	C								
-8.00		C	C	C	C	C	C	C	C								
-8.25		C	C	C	C	C	C	C	C								
-8.50		C	C	C	C	C	C	C	C								
-8.75		C	C	C	C	C	C	C	C								
-9.00		C	C	C	C	C	C	C	C								
-9.25		C	C	C	C	C	C	C	C								
-9.50		C	C	C	C	C	C	C	C								
-9.75		C	C	C	C	C	C	C	C								
-10.00		C	C	C	C	C	C	C	C								

A: Ø65 mm

B: Ø65 / Ø70 mm

C: Ø70 mm

D: Ø72 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

CYL 0.00 is not inferred where the source specifies negative CYL only.

SELECT Clear Vision 1.56 Mid Index SPH

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Plus SPH

UV400 | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
+0.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+0.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+0.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+1.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+1.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+1.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+1.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+2.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+2.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+2.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+2.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+3.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+3.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+3.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+3.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+4.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+4.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+4.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+4.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+5.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+5.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+5.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+5.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+6.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+6.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+6.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+6.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+7.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+7.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+7.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+7.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+8.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+8.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+8.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+8.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+9.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+9.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+9.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+9.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+10.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

A: Ø65 mm

B: Ø65 / Ø70 mm

C: Ø70 mm

D: Ø72 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

CYL 0.00 is not inferred where the source specifies negative CYL only.

SELECT Clear Vision 1.56 Mid Index SPH

Finished | SPH

UV400 | Made in China

CYL (- ON -) - 0.25 ~ - 4.00					POWER	CYL (+ ON -) - 0.25 ~ - 4.00						
DIA-(mm)	E/T (mm)	C/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	DIA-(mm)	C/T (mm)	E/T (mm)	DIA-(mm)
Ø72 CYL -0.25 to -2.00 Ø70 CYL -2.25 to -4.00	2.1	2	4.00	4.00	PLANO							
	2.3	2		3.75	0.25	4.25	4.00	2.00	Ø70 (a)	1.8	1.7	Ø65
	2.8	2		3.50	0.5	4.50		2.30		2.1	1.6	
	2.8	1.8		3.25	0.75	4.75		2.40			1.6	
	3.1	1.8		3.00	1	5.00		2.70		2.4	1.6	
	3.3	1.6		2.75	1.25	4.25	3.00	2.50		2.4	1.2	
	3.5	1.6		2.50	1.5	4.50		2.80		2.6	1.2	
	3.8	1.4	5.00	3.25	1.75	4.75		3.20		2.9	1.2	
	4.1	1.4		3.00	2	5.00		3.40		3.1	1.2	
	4.2	1.2		2.75	2.25	5.25		3.70	Ø70	3.4	1.2	Ø65
	4.5			2.50	2.5	5.5		4.10		3.7	1.2	
	4.8			2.25	2.75	5.75		4.40		3.9	1.2	
	5.1			2.00	3	6		4.70		4.2	1.2	
	5.4		5.50	2.25	3.25	5.25	2.00	4.80		4.4	1.1	
	5.7			2.00	3.5	5.5		5.10		4.6		
	6			1.75	3.75	5.75		5.40		4.9		
	6.3			1.50	4	6		5.70		5.1		
	6.6			1.25	4.25	6.25		6.10	Ø70	5.4		Ø65
	6.9			1.00	4.5	6.5		6.40		5.6		
	7.2		6.50	1.75	4.75	6.75		6.60		5.9		
	7.6			1.50	5	7		7.00		6.1		
	7.8			1.25	5.25	7.25		7.20		6.3		
	8.1			1.00	5.5	7.5		7.50		6.6		
	8.4			0.75	5.75	7.75		7.90		6.8		
	8.7			0.50	6	8		8.30		7.1		
Ø70 CYL -0.25 to -2.00	8.8	1.2	7.50	1.25	6.25	7.25	1			7.78	1.6	Ø65
	9.1			1.00	6.5	7.5				8.02		
	9.4			0.75	6.75	7.75				8.28		
	9.7			0.50	7	8				8.5		
	9.8		8.50	1.25	7.25	8.25				8.76		
	10.2			1.00	7.5	8.5				9.02		
	10.6			0.75	7.75	8.75				9.31		
	11.1			0.50	8	9				9.52		
	11.6		9.50	1.25	8.25	9.25				9.78		
	11.9			1.00	8.5	9.5				10.06		
	12.3			0.75	8.75	9.75				10.32		
	12.7			0.50	9	10				10.61		
	13.2		10.50	1.25	9.25	10.25				10.85		
	13.5			1.00	9.5	10.5				11.16		
	13.8			0.75	9.75	10.75				11.36		
	14			0.50	10	11				11.68		

(a) Ø70 mm: front/rear curves and edge thickness follow Ø65 mm.

Thickness tolerance: +/- 0.3 mm (centre and edge)

MINUS LENS

SPH 0.00 to -6.00 / CYL -0.25 to -4.00

SPH -6.25 to -8.00 / CYL -0.25 to -2.00

SPH -8.25 to -10.00

PLUS LENS

SPH +0.25 to +10.00

CYL -0.25 to -4.00