SELECT Clear Vision 1.60 MR-8 SPH

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Minus SPH

UV400 | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
0.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-0.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-0.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-0.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-1.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-1.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-1.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-1.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-6.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-6.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-6.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-6.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-8.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-8.25		C	C	C	C	C	C	C	C								
-8.50		C	C	C	C	C	C	C	C								
-8.75		C	C	C	C	C	C	C	C								
-9.00		C	C	C	C	C	C	C	C								
-9.25		C	C	C	C	C	C	C	C								
-9.50		C	C	C	C	C	C	C	C								
-9.75		C	C	C	C	C	C	C	C								
-10.00		C	C	C	C	C	C	C	C								
-10.25	C																
-10.50	C																
-10.75	C																
-11.00	C																
-11.25	C																
-11.50	C																
-11.75	C																
-12.00	C																

A: Ø60 / Ø65 / Ø70 mm

B: Ø65 mm

C: Ø70 mm

D: Ø75 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

SPH-only delivery at -10.25 to -12.00 D is explicitly documented in the catalogue.

SELECT Clear Vision 1.60 MR-8 SPH

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Plus SPH

UV400 | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
+0.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+0.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+0.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+1.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+1.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+1.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+1.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+2.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+2.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+2.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+2.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+3.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+3.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+3.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+3.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+4.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+4.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+4.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+4.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+5.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+5.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+5.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+5.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+6.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+6.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+6.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+6.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+7.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+7.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+7.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+7.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+8.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B

A: Ø60 / Ø65 / Ø70 mm

B: Ø65 mm

C: Ø70 mm

D: Ø75 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

SPH-only delivery at -10.25 to -12.00 D is explicitly documented in the catalogue.

SELECT Clear Vision 1.60 MR-8 SPH

Finished | SPH | Minus technical specifications

MR-8 | UV400 | Made in China

SPH (D)	Diameter (mm)	Front Curve (D)	Back Curve (D)	CT (mm)	ET (mm)
0.00	75	4.50	4.50	2.00	2.00
-0.25	75	4.25	4.50	1.80	2.20
-0.50	75	4.00	4.50	1.70	2.40
-0.75	75	3.75	4.50	1.70	2.70
-1.00	75	3.50	4.50	1.60	2.90
-1.25	75	3.70	5.00	1.50	3.30
-1.50	75	3.50	5.00	1.40	3.50
-1.75	75	3.25	5.00	1.15	3.60
-2.00	75	3.00	5.00	1.15	3.90
-2.25	75	3.25	5.50	1.15	3.80
-2.50	75	3.00	5.50	1.15	4.10
-2.75	75	2.75	5.50	1.15	4.40
-3.00	75	2.50	5.50	1.15	4.70
-3.25	75	2.75	6.00	1.15	5.00
-3.50	75	2.50	6.00	1.15	5.30
-3.75	75	2.25	6.00	1.15	5.60
-4.00	75	2.00	6.00	1.15	6.10
-4.25	75	2.25	6.50	1.15	6.20
-4.50	75	2.00	6.50	1.15	6.60
-4.75	75	1.75	6.50	1.15	6.90
-5.00	75	1.50	6.50	1.15	7.30
-5.25	75	2.25	7.50	1.15	7.60
-5.50	75	2.00	7.50	1.15	7.90
-5.75	75	1.75	7.50	1.15	8.20
-6.00	75	1.50	7.50	1.15	8.50
-6.25	70	2.00	8.25	1.15	8.00
-6.50	70	1.75	8.25	1.15	8.30
-6.75	70	1.50	8.25	1.15	8.50
-7.00	70	1.25	8.25	1.15	8.70
-7.25	70	1.00	8.25	1.15	9.10
-7.50	70	0.75	8.25	1.15	9.30
-7.75	70	1.50	9.25	1.15	9.90
-8.00	70	1.25	9.25	1.15	10.10
-8.25	70	1.00	9.25	1.15	10.40
-8.50	70	0.75	9.25	1.15	10.60
-8.75	70	0.50	9.25	1.15	11.00
-9.00	70	0.25	9.25	1.15	11.20
-9.25	70	1.00	10.25	1.15	11.50
-9.50	70	0.75	10.25	1.15	11.90
-9.75	70	0.50	10.25	1.15	12.20
-10.00	70	0.25	10.25	1.15	12.50
-10.25	70	1.00	11.25	1.15	12.60
-10.50	70	0.75	11.25	1.15	13.00
-10.75	70	0.50	11.25	1.15	13.30
-11.00	70	0.25	11.25	1.15	13.60
-11.25	70	1.00	12.25	1.15	13.80
-11.50	70	0.75	12.25	1.15	14.20
-11.75	70	0.50	12.25	1.15	14.50
-12.00	70	0.25	12.25	1.15	14.80

NOTES

CT = centre thickness. ET = edge thickness. Thickness tolerance: ±0.30 mm.

SPH 0.00 to -8.00: CYL -0.25 to -4.00 D; -8.25 to -10.00: CYL -0.25 to -2.00 D.

SPH -10.25 to -12.00: CYL stated as not available; geometry retained as reference.

SELECT Clear Vision 1.60 MR-8 SPH

Finished | SPH | Plus technical specifications

MR-8 | UV400 | Made in China

SPH (D)	Front Curve (D)	Back Curve (D)	Centre thickness CT (mm)			Edge thickness ET (mm)	
			Ø60	Ø65	Ø70	Ø65	Ø70
+0.25	4.75	4.50	2.10	2.10	2.20	—	1.90
+0.50	5.00	4.50	1.75	1.90	1.90	—	1.40
+0.75	5.25	4.50	1.75	1.90	2.00	—	1.20
+1.00	5.50	4.50	1.85	2.00	2.10	—	1.10
+1.25	5.75	4.50	2.05	2.30	2.40	—	1.10
+1.50	6.00	4.50	2.25	2.50	2.70	—	1.10
+1.75	6.25	4.50	2.45	2.70	2.90	—	1.10
+2.00	6.50	4.50	2.65	3.00	3.20	—	1.10
+2.25	5.35	3.10	2.80	3.20	3.45	1.10	1.10
+2.50	5.60	3.10	3.00	3.40	3.70	1.10	1.10
+2.75	5.85	3.10	3.20	3.60	4.00	1.10	1.10
+3.00	6.10	3.10	3.40	3.80	4.25	1.10	1.10
+3.25	6.35	3.10	3.60	4.00	4.50	1.10	1.10
+3.50	6.60	3.10	3.80	4.30	4.80	1.10	1.10
+3.75	6.85	3.10	3.95	4.50	5.05	1.10	1.10
+4.00	7.10	3.10	4.15	4.70	5.35	1.10	1.10
+4.25	5.15	0.90	4.30	4.90	5.45	1.10	1.10
+4.50	5.40	0.90	4.45	5.10	5.70	1.10	1.10
+4.75	5.65	0.90	4.65	5.40	6.00	1.10	1.10
+5.00	5.90	0.90	4.85	5.60	6.25	1.10	1.10
+5.25	6.15	0.90	5.05	5.80	6.50	1.10	1.10
+5.50	6.40	0.90	5.25	6.00	6.80	1.10	1.10
+5.75	6.65	0.90	5.40	6.20	7.05	1.10	1.10
+6.00	6.90	0.90	5.60	6.40	7.30	1.10	1.10
+6.25	7.15	0.90	—	6.60	—	1.10	—
+6.50	7.35	0.90	—	6.90	—	1.10	—
+6.75	7.55	0.90	—	7.10	—	1.10	—
+7.00	7.75	0.90	—	7.30	—	1.10	—
+7.25	7.95	0.90	—	7.60	—	1.10	—
+7.50	8.15	0.90	—	7.80	—	1.10	—
+7.75	8.35	0.90	—	8.10	—	1.10	—
+8.00	8.55	0.90	—	8.30	—	1.10	—

NOTES

— = no diameter-specific value documented. Thickness tolerance: ±0.30 mm.

ET for Ø60 is not specified.

Plus supply range: SPH +0.25 to +8.00 D | CYL -0.25 to -4.00 D.