SELECT Clear Vision 1.60 MR-8 AS

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Minus SPH

UV400 | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
0.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-0.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-0.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-0.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-1.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-1.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-1.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-1.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-2.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-3.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-4.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.25		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.50		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-5.75		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-6.00		D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D
-6.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-6.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-6.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-7.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-8.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-8.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-8.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-8.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-9.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-9.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-9.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-9.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-10.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-10.25	C																
-10.50	C																
-10.75	C																
-11.00	C																
-11.25	C																
-11.50	C																
-11.75	C																
-12.00	C																

A: Ø65 mm

B: Ø65 / Ø70 mm

C: Ø70 mm

D: Ø75 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

SELECT Clear Vision 1.60 MR-8 AS

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Plus SPH

UV400 | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00	-2.25	-2.50	-2.75	-3.00	-3.25	-3.50	-3.75	-4.00
+0.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
+0.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
+0.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
+1.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
+1.25		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
+1.50		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
+1.75		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
+2.00		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
+2.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+2.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+2.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+3.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+3.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+3.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+3.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+4.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+4.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+4.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+4.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+5.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+5.25		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+5.50		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+5.75		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+6.00		B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
+6.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+6.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+6.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+7.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+7.25		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+7.50		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+7.75		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
+8.00		A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

A: Ø65 mm

B: Ø65 / Ø70 mm

C: Ø70 mm

D: Ø75 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

SELECT Clear Vision 1.60 MR-8 AS

Finished | AS | Minus technical specifications

MR-8 | UV400 | Made in China

SPH (D)	Diameter (mm)	Front Curve (D)	Back Curve (D)	CT (mm)	ET (mm)
0.00	75	4.25	4.25	2.00	2.00
-0.25	75	4.00	4.25	1.80	2.30
-0.50	75	3.75	4.25	1.70	2.50
-0.75	75	3.50	4.25	1.60	2.60
-1.00	75	3.25	4.25	1.60	2.90
-1.25	75	3.00	4.25	1.50	3.10
-1.50	75	2.75	4.25	1.40	3.40
-1.75	75	2.50	4.25	1.15	3.40
-2.00	75	2.25	4.25	1.15	3.60
-2.25	75	3.00	5.25	1.15	4.00
-2.50	75	2.75	5.25	1.15	4.20
-2.75	75	2.50	5.25	1.15	4.30
-3.00	75	2.25	5.25	1.15	4.60
-3.25	75	2.00	5.25	1.15	4.70
-3.50	75	1.75	5.25	1.15	5.20
-3.75	75	1.50	5.25	1.15	5.50
-4.00	75	1.25	5.25	1.15	5.80
-4.25	75	2.00	6.25	1.15	6.20
-4.50	75	1.75	6.25	1.15	6.40
-4.75	75	1.50	6.25	1.15	6.70
-5.00	75	1.25	6.25	1.15	7.00
-5.25	75	1.00	6.25	1.15	7.40
-5.50	75	0.75	6.25	1.15	7.70
-5.75	75	0.50	6.25	1.15	7.90
-6.00	75	0.25	6.25	1.15	8.20
-6.25	70	2.00	8.25	1.15	7.90
-6.50	70	1.75	8.25	1.15	8.20
-6.75	70	1.50	8.25	1.15	8.30
-7.00	70	1.25	8.25	1.15	8.50
-7.25	70	1.00	8.25	1.15	8.80
-7.50	70	0.75	8.25	1.15	9.10
-7.75	70	0.50	8.25	1.15	9.30
-8.00	70	0.25	8.25	1.15	9.60
-8.25	70	1.00	9.25	1.15	10.20
-8.50	70	0.75	9.25	1.15	10.50
-8.75	70	0.50	9.25	1.15	10.60
-9.00	70	0.25	9.25	1.15	10.90
-9.25	70	0.75	10.00	1.15	11.40
-9.50	70	0.50	10.00	1.15	11.60
-9.75	70	0.25	10.00	1.15	11.90
-10.00	70	0.00	10.00	1.15	12.30
-10.25	70	0.75	11.00	1.15	12.50
-10.50	70	0.50	11.00	1.15	12.70
-10.75	70	0.25	11.00	1.15	13.00
-11.00	70	0.00	11.00	1.15	13.40
-11.25	70	0.75	12.00	1.15	13.60
-11.50	70	0.50	12.00	1.15	13.80
-11.75	70	0.25	12.00	1.15	14.10
-12.00	70	0.00	12.00	1.15	14.50

NOTES

CT = centre thickness. ET = edge thickness. Thickness tolerance: ±0.30 mm.

Source CYL range: -0.25 to -4.00 D up to SPH -10.00 D.

Any further geometry rows are technical reference data, not an extended supply range.

SELECT Clear Vision 1.60 MR-8 AS

Finished | AS | Plus technical specifications

MR-8 | UV400 | Made in China

SPH (D)	Front Curve (D)	Back Curve (D)	Centre thickness CT (mm)		Edge thickness ET (mm)	
			Ø65	Ø70	Ø65	Ø70
+0.25	3.75	3.50	—	2.10	—	1.90
+0.50	4.00	3.50	—	2.20	—	1.60
+0.75	4.25	3.50	—	1.80	—	1.40
+1.00	4.50	3.50	—	1.90	—	1.40
+1.25	4.75	3.50	—	2.00	—	1.10
+1.50	5.00	3.50	—	2.20	—	1.10
+1.75	5.25	3.50	—	2.50	—	1.10
+2.00	5.50	3.50	—	2.70	—	1.10
+2.25	4.75	2.50	2.70	3.20	1.10	1.10
+2.50	5.00	2.50	2.90	3.40	1.10	1.10
+2.75	5.25	2.50	3.10	3.70	1.10	1.10
+3.00	5.50	2.50	3.30	4.00	1.10	1.10
+3.25	5.75	2.50	3.60	4.20	1.10	1.10
+3.50	6.00	2.50	3.80	4.40	1.10	1.10
+3.75	6.25	2.50	4.00	4.70	1.10	1.10
+4.00	6.50	2.50	4.30	5.00	1.10	1.10
+4.25	5.25	1.00	4.30	5.20	1.10	1.10
+4.50	5.50	1.00	4.60	5.40	1.10	1.10
+4.75	5.75	1.00	4.80	5.70	1.10	1.10
+5.00	6.00	1.00	5.10	6.00	1.10	1.10
+5.25	6.25	1.00	5.30	6.30	1.10	1.10
+5.50	6.50	1.00	5.50	6.50	1.10	1.10
+5.75	6.75	1.00	5.70	6.80	1.10	1.10
+6.00	7.00	1.00	5.90	7.10	1.10	1.10
+6.25	7.25	1.00	6.40	—	1.10	—
+6.50	7.45	1.00	6.70	—	1.10	—
+6.75	7.65	1.00	6.90	—	1.10	—
+7.00	7.85	1.00	7.10	—	1.10	—
+7.25	8.05	1.00	7.30	—	1.10	—
+7.50	8.25	1.00	7.60	—	1.10	—
+7.75	8.45	1.00	7.80	—	1.10	—
+8.00	8.65	1.00	8.10	—	1.10	—

NOTES

— = no diameter-specific value documented. Thickness tolerance: ±0.30 mm.

Plus supply range: SPH +0.25 to +8.00 D | CYL -0.25 to -4.00 D.