SELECT ADAPTIVE 1.56

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Minus SPH

UV400 | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00
0.00		B	B	B	B	B	B	B	B
-0.25		B	B	B	B	B	B	B	B
-0.50		B	B	B	B	B	B	B	B
-0.75		B	B	B	B	B	B	B	B
-1.00		B	B	B	B	B	B	B	B
-1.25		B	B	B	B	B	B	B	B
-1.50		B	B	B	B	B	B	B	B
-1.75		B	B	B	B	B	B	B	B
-2.00		B	B	B	B	B	B	B	B
-2.25		B	B	B	B	B	B	B	B
-2.50		B	B	B	B	B	B	B	B
-2.75		B	B	B	B	B	B	B	B
-3.00		B	B	B	B	B	B	B	B
-3.25		B	B	B	B	B	B	B	B
-3.50		B	B	B	B	B	B	B	B
-3.75		B	B	B	B	B	B	B	B
-4.00		B	B	B	B	B	B	B	B
-4.25		B	B	B	B	B	B	B	B
-4.50		B	B	B	B	B	B	B	B
-4.75		B	B	B	B	B	B	B	B
-5.00		B	B	B	B	B	B	B	B
-5.25		B	B	B	B	B	B	B	B
-5.50		B	B	B	B	B	B	B	B
-5.75		B	B	B	B	B	B	B	B
-6.00		B	B	B	B	B	B	B	B
-6.25		B	B	B	B	B	B	B	B
-6.50		B	B	B	B	B	B	B	B
-6.75		B	B	B	B	B	B	B	B
-7.00		B	B	B	B	B	B	B	B
-7.25		B	B	B	B	B	B	B	B
-7.50		B	B	B	B	B	B	B	B
-7.75		B	B	B	B	B	B	B	B
-8.00		B	B	B	B	B	B	B	B
-8.25	B								
-8.50	B								
-8.75	B								
-9.00	B								
-9.25	B								
-9.50	B								
-9.75	B								
-10.00	B								

A: Ø65 mm

B: Ø70 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

SELECT ADAPTIVE 1.56

Available coatings: UC / HC / HMC / HMC+

Finished | Power Range | Plus SPH

UV400 | Made in China

SPH (D)	0.00	-0.25	-0.50	-0.75	-1.00	-1.25	-1.50	-1.75	-2.00
+0.25		A	A	A	A	A	A	A	A
+0.50		A	A	A	A	A	A	A	A
+0.75		A	A	A	A	A	A	A	A
+1.00		A	A	A	A	A	A	A	A
+1.25		A	A	A	A	A	A	A	A
+1.50		A	A	A	A	A	A	A	A
+1.75		A	A	A	A	A	A	A	A
+2.00		A	A	A	A	A	A	A	A
+2.25		A	A	A	A	A	A	A	A
+2.50		A	A	A	A	A	A	A	A
+2.75		A	A	A	A	A	A	A	A
+3.00		A	A	A	A	A	A	A	A
+3.25		A	A	A	A	A	A	A	A
+3.50		A	A	A	A	A	A	A	A
+3.75		A	A	A	A	A	A	A	A
+4.00		A	A	A	A	A	A	A	A
+4.25		A	A	A	A	A	A	A	A
+4.50		A	A	A	A	A	A	A	A
+4.75		A	A	A	A	A	A	A	A
+5.00		A	A	A	A	A	A	A	A
+5.25		A	A	A	A	A	A	A	A
+5.50		A	A	A	A	A	A	A	A
+5.75		A	A	A	A	A	A	A	A
+6.00		A	A	A	A	A	A	A	A

A: Ø65 mm

B: Ø70 mm

White cells: no combination documented for this product.

CYL values are shown in D. Reference geometry follows on subsequent pages.

SELECT ADAPTIVE 1.56

Finished | SPH | Ø65 / 70 mm

UV400 | Made in China

Technical index: 1.545

CYL (- ON -) - 0.25 ~ - 4.00					POWER	CYL (+ON -) - 0.25 ~ - 4.00				
DIA (mm)	E/T (mm)	C/T (mm)	BACK BASE	FRONT BASE		FRONT BASE	BACK BASE	C/T (mm)	E/T (mm)	DIA (mm)
Ø70	2.1	2	4	4	PLANO					
	2.3	2		3.75	0.25	4.25	4	1.8	1.7	Ø65
	2.8	2		3.5	0.5	4.5		2.1	1.6	
	3	2		3.25	0.75	4.75		2.1	1.6	
	3.3	2		3	1	5		2.4	1.6	
	3.5	1.8		2.75	1.25	4.25	3	2.4	1.2	
	3.7	1.8		2.5	1.5	4.5		2.6	1.2	
	4.2	1.8	5	3.25	1.75	4.75		2.9	1.2	
	4.5	1.8		3	2	5		3.1	1.2	
	4.8	1.8		2.75	2.25	5.25		3.4	1.2	Ø65
	5.1	1.8		2.5	2.5	5.5		3.7	1.2	
	5.4	1.8		2.25	2.75	5.75		3.9	1.2	
	5.7	1.8		2	3	6		4.2	1.2	
	6	1.8	5.5	2.25	3.25	5.25	2	4.4	1.1	
	6.3	1.8		2	3.5	5.5		4.6		
	6.6	1.8		1.75	3.75	5.75		4.9		
	6.9	1.8		1.5	4	6		5.1		
	7	1.6		1.25	4.25	6.25		5.4		Ø65
	7.3			1	4.5	6.5		5.6		
	7.5		6.5	1.75	4.75	6.75		5.9		
	8			1.5	5	7		6.1		
	8.2			1.25	5.25	7.25		6.3		
	8.5			1	5.5	7.5		6.6		
	8.9			0.75	5.75	7.75		6.8		
	9.1			0.5	6	8		7.1		
Ø70	9.2	1.6	7.5	1.25	6.25	**TOLERANCE (+/- 0. 3 mm)** CENTER- EDGE THICKNESS **1. "MINUS" LENS** SPH AXIS : 0.00 ~ -8.00 CYL AXIS : -0.25 ~ -2.00 SPH AXIS : -8.25 ~ -10.00 CYL AXIS :0.00 **2."PLUS"LENS** SPH AXIS:+0.25~+6.00 CYL AXIS : -0.25 ~ -2.00				
	9.5			1	6.5					
	9.8			0.75	6.75					
	10.1			0.5	7					
	10.2		8.5	1.25	7.25					
	10.6			1	7.5					
	11			0.75	7.75					
	11.5			0.5	8					
Ø70			9.5	1.25	8.25					
				1	8.5					
				0.75	8.75					
				0.5	9					
			10.5	1.25	9.25					
				1	9.5					
				0.75	9.75					
				0.5	10					